

GRAYSTAR[★] LLC

Ceramic Minerals and Specialty Materials

Sales Office

8500 Sheridan Dr
Williamsville, NY 14221
Phone: 716-633-0077
Fax: 716-633-0099
Quality Manager: rprevite@graystarllc.com

Headquarters

9 Simmonsville Rd
PO Box 1670
Bluffton, SC 29910
Phone: 843-815-5600
Fax: 843-815-5601

Technical Data Sheet

Product: NorZon® Alumina Zirconia (40%)

Description: NZ Alundum is a hard, very tough, sharp abrasive. It is produced by fusing zircon sand and alumina at about 1900°C.

Applications: NorZon® is used for both coated abrasive products and organic bonded grinding wheels.

Typical Chemical Analysis:

Aluminum Oxide (Al ₂ O ₃)	60.00%
Zirconium Oxide (ZrO ₂)	39.00%
Titanium Dioxide (TiO ₂)	0.25%
Silicon Dioxide (SiO ₂)	0.35%
Iron Oxide (Fe ₂ O ₃)	0.25%
Sodium Oxide (Na ₂ O)	0.03%
Calcium Oxide (CaO)	0.09%
Magnesium Oxide (MgO)	0.02%

Physical Characteristics:

Crystal Size:	12 Microns
True Density:	4.60 g/cm ³
Hardness:	Knoop 1600, Mohs 9.0
Melting Point:	1900°C
Loose Pack Density:	1.90 – 2.30 g/cm ³
Bulk Density Range:	126 – 146 lbs/ft ³

ANSI Test Methods:

Chemistry:	B74.14
Sizing:	B74.12
Bulk Density:	B74.4

Packaging & Shipping:

Warehousing in Bluffton, SC and Niagara Falls, NY
400 lb. fiber drums grade sizes 8 – 120
2000 lb. supersacks
Plastic pails, etc. for a surcharge (SC only)

Manufacturers and Distributors of Abrasive Materials